

FRONT OR REAR MOUNTED SWEEPER

PTMH 24"



- The PTMH sweeps when being pushed or pulled
- PTO mechanically driven sweeper
- Brush diameter 24"
- The PTMH24 model is recommended to be installed on a tractor or front-mount mowers

Standard features

General

- Anchor rings for handling and transportation
- PTO of 540 or 2000 RPM and more
- 1 double-action flow control for hydraulic angulation (option)
- 2-point, 3-point or Kubota hitch adapter
- Weight 5' = 465 lbs
- Weight 6' = 510 lbs

Brush Drive

- The sweeper can be installed on equipment with 25 HP or more
- PTO brush drive
- The brush is supported by two ball bearings
- Manual or hydraulic angulation of 25° on each side

Brush (model PTMH24)

- Replaceable disc brush, exterior diameter 24" with a 6 3/8" interior diameter (core).
- Choice of brushes: polypropylene only or polypropylene / wire
- Brush width: 54", 5', 6', 7'

Standard features

Structure

- Laser cut parts for a smoother finish and design
- Tubular structure, robust construction
- 16-gauge steel hood covering 180° of the brush

Finish

- Powder coat
- All parts are individually painted

Wheels

- Two 6" load bearing wheels behind the sweeper

Options

Hydraulic angulation (25 degrees)

- Hydraulic angulation

